

Derusting Series - Electric

Applications:

The Derusting Series are used for the following:

- Tank cleaning
- Ship hull cleaning
- Marine surface prep
- Derusting
- Clear oyster
- Descaling
- Deck cleaning

General Features:

- Triplex pump with 3/5 ceramic plungers
- Unloader valve, with by-pass system, infinitely variable volume and pressure
- Stainless steel liquid filled pressure gauge
- Micro Water Filter
- Lack of water protection
- Temperature protection
- Motor with thermal protection
- Industrial motor, S1, IP55, F, with 100% running time (24h running)
- Pump and motor separated by flexible clutch
- Wheel heavy trolley mounted unit, epoxy painting

Standard Accessories:

- High pressure hose, 20m
- Spray gun
- Flat spray nozzle, 15°
- Straight jet nozzle
- Cable: 5m
- Inlet hose: 5m



HP500



HP800S/HP1000S/HP1250

Technical Data		HP500	HP800S	HP1000S	HP1250
Pressure	Bar/psi	500/7250	800/11600	1000/14500	1250/18000
Flow	L/min	33	24	18	18
Power Rating	Kw	33.5	33.5	33.5	41.5
Power Supply		440V/3P 60Hz	440V/3P 60Hz	440V/3P 60Hz	440V/3P 60Hz
Weight	Kg	425	515	515	565
Dimensions	mm	1270x700x1000	1270x700x1000	1270x700x1000	1270x700x1000
Code		0120009	0120020	0120021	0120026